

CLAIMS

1. A resin composition
which comprises a resin (A) and a resin (B) as
5 constituents,

said resin (A) having a number average molecular weight
of 1,000 to 35,000 and

being at least one member selected from the group
consisting of following (A1) and (A2):

10 (A1) a polyester polyol, a polyether polyol, a polycarbonate
polyol, a polyurethane polyol, a polyolefin polyol and an
acrylic polyol,

(A2) a polymer obtained by reacting said (A1) with a compound
having at least one functional group selected from the group
15 consisting of isocyanato, carboxyl and epoxy groups within a
molecule thereof, a dialkyl carbonate, a cyclic carbonate, an
alcohol, or a mixture of these, and

said resin (B) having a sulfonium group and a propargyl
group within the molecule thereof.

20

2. The resin composition according to Claim 1,
wherein the resin (A) has an unsaturated functional
group.

25

3. The resin composition according to Claim 2,
wherein a polybutadiene derivative is used as a source
of introduction of the unsaturated functional group into the
resin (A).

30

Sub A1 → 4. The resin composition according to Claim 2 or 3,
wherein a compound having an unsaturated triple bond is
used as the source of introduction of the unsaturated functional
group into the resin (A) in an amount of 1 to 50% by weight based
on the solid matter in the resulting resin (A).

35

Sub A 7

5. The resin composition according to Claim 1, 2, 3 or
 4,
 wherein the resin (A) occupies 5 to 80% by weight based
 on the total resin solid matter of the resin (A) and the resin
 5 (B).

6. A cationic electrodeposition coating composition
 which comprises the resin composition according to Claim
 1, 2, 3, 4 or 5.

10

add A2

09922013-112501